


# **Increase Efficiency with More Strength and Longer Tire Life**

**VPCS** provides enhanced productivity thanks to increased loading capacity, as well as improved durability and longer tire life.


## More Efficient Operations, Productivity-Enhancing Solutions


With the load index of 204 for 450/95R25 and 208 for the 480/95R25, the VPCS delivers high load capacity in all speed ranges. In addition with the maximum speed increased vs the 16.00R25 VCHR, the VPCS realizes efficient operations at your port.



## **Longer Tire Life**

Realized thanks to new pattern and casing, enabling extraordinary wear performance and prevention of sudden failures.





# Applied Technologies New Pattern Wear life and tread durability improvement VCHR VPCS Improved casing durability

### **Specifications**

The 480/95R25 can be fitted on both 13.00/2.5 Rim and 11.25/2.0 Rim enabling smoother stock management and operational simplicity.

Tire Size	LI/SS	Туре	Recommended Rim/Flange Height Approved Rim/Flange Height	Approximate Inflated Dimensions				ОТД
				OD	ow	SLR	SLW	
			inch	mm	mm	mm	mm	mm
450/95R25	204A5	T/L	11.25/2.0	1504	443	658	520	45
480/95R25	208A5	T/L	13.00/2.5 11.25/2.0	1548	485	683	557	45

T/L: Tubeless type, OD: Overall Diameter, OW: Overall Width, SLR: Static Loaded Radius, SLW: Static Loaded Width, OTD: Original Tread Depth

## USE OF THIS PRODUCT OTHER THAN FOR INTENDED PURPOSES IS STRICTLY PROHIBITED



VPCS aligns with the Bridgestone E8 Commitment that consists of 8 Bridgestone-like values starting with the letter "E" (Energy, Ecology, Efficiency, Extension, Economy, Emotion, Ease, and Empowerment) to contribute to realizing a sustainable society.

**Bridgestone Corporation**For your nearest Bridgestone Authorized Dealer, visit our web site

https://www.bridgestone.com/products/off\_the\_road/

